



## ALIZE 6000 E UK

PORTABLE POWER


Gamme 50Hz UK Prestige

### Product advantages

- ➔ Full control panel
- ➔ electric start
- ➔ Large Autonomy
- ➔ OHV Honda engine
- ➔ Very Silent

### Divers

The top quality alliance of performance and soundproofing.



This product is QUALIGEN certified. Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After Sales Service) in order to provide the highest level of quality of our and thus to guarantee the users safety.

## ALIZE 6000 E UK

### General specifications

Range	Prestige
Frequency (Hz)	50
Max. power (kW)	5.6
Max power. (kVA)	6.05
Nominal voltage (V)	230
Number of phase	Single phase - 230V
Acoustic pressure level Lw(A)	91
Noise level dB(A) - 1m	78
Noise level dB(A) - 7m	68

### Engine specifications

Engine trademark	Honda
Engine type	GX 390
Distribution	O.H.V.
Start	Electrical
Fuel	Petrol (unlead)
Autonomy (h)	9.6
Consumption (L/h]	2.5
Tank (L)	24
Oil Guard	Yes
Capacity (cm3)	389
Oil capacity (L)	1.1

### Alternator specifications

Type	Without collar or brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	H

### Plugs and panel descriptive

1 x 2P+T 115V 16A - disjoncteur + 1 x 2P+T 115V 32A - disjoncteur + 1 x 2P+T 230V 16A - disjoncteur + 1 x 2P+T 230V 32A - disjoncteur + compteur horaire + voyant

### Dimensions and weight

Lenght (cm)	78
Width (cm)	59
Height (cm)	75
Dry Weight (kgs)	130

### Packaging

Packaging type	Box / Pallet
Length (cm)	80
Width (cm)	61
Height (cm)	78.5
Pallet type	120/80
Number of box by pallet	4
Pallet height (cm)	164

**Accessories**

	<b>R05C</b>	<b>Automatic mains failure panel R05C</b>	Automatic start (including charger, normal/backup inverter).
	<b>R50</b>	<b>Male plugs 230V/16A R50</b>	16A blue 230V male plug - Sold per 1 or 10
	<b>R51</b>	<b>Male plugs 115V/16A R51</b>	16A yellow 115V male plug - Sold per 1 or 10
	<b>R52</b>	<b>Male plugs 230V/32A R52</b>	32A blue 230V male plug - Sold per 1 or 5
	<b>R53</b>	<b>Male plugs 115V/32A R53</b>	32A yellow 115V male plug - Sold per 1 or 5
	<b>R54</b>	<b>R54 adaptor kit</b>	Adaptator R54 16A/13A adaptor unit. Sold per 1 or 3
	<b>R55</b>	<b>R55 adaptor kit</b>	ADAPTATOR R55 16A/13A adaptor economy. Sold per 1 or 3
	<b>R56</b>	<b>R56 adaptor kit</b>	ADAPTATOR R56 16A/13A double adaptor. Sold per 1 or 3
	<b>RBH1</b>	<b>Cans of oil RBH1</b>	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
	<b>RBH0-5</b>	<b>Cans of oil RBH0-5</b>	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).
	<b>RPQ</b>	<b>Earth spike RPQ</b>	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm <sup>2</sup> cable.