



PORTABLE POWER
Welding sets
VX200-4H-2-UK
Range **Weldarc**

Solid and compact frame
OHV Honda professional engine
Storage rack
Welding quality
Oil level safety

Welding sets which can be used on sites where there is no electricity

General specifications	
Fréquency [Hz]	50
Max power [kW]	4
Intensive welding rate 60% [A]	170
Type of current	Continuous
Priming voltage [V]	75
Mini/maxi rods diameter[mm]	1.6/4
Noise level Lwa [dB(A)]	97
Noise level dB(A) @7m	74

Alternator specifications	
Type	
Regulation	Mecanichal
Protection class	IP 23
Insulation class	Class H

Engine specifications	
Brand	Honda
Type	GX 390
Distribution	O.H.V.
Starting	Hand start
Fuel	Unleaded petrol
Run time [h]	2.7
Fuel consumption [l/h]	2.4
Tank [l]	6.5
Oil guard	Yes
Cubic capacity [cm3]	389
Oil capacity [l]	1.1

Sockets and panel
1 x 2P+T 115V 16A - circuit breaker + 1 x 2P+T 230V 16A - circuit breaker

Dimensions and weight	
L x l x h dimensions [cm]	87 x 57 x 55.5
Weight [kgs]	87

Packaging	
Packaging	Carton / Pallet
Dim Unit(Cm)	88.0x58.5x70.0
Cartons by Pal 120/80	4
Cartons by Pal 140/110	NA
Height Of Pallet (cm)	147

Options



Trolley kit R07

R07 : For gensets > 3 kW : its system with 4 handling bars avoids handling problems - Last version with new wheels (diameter 300 mm)



Maintenance kits for HONDA engines R17-R18-R19

10 maintenance kits for Honda engines including oil, spark plug and air filter : Type GC135 : Réf. R17 - Type GX200 (sauf SH3000) : Réf. R18 - Type GX270 & GX390 (sauf SH4000) : Réf R19



Male sockets 230V/16A R50

R50 : 230 V / 16 A blue male plug sold per one or 10



Male sockets 115V/16A R51

R51 : 115 V / 16 A Yellow male plug sold per one or 10



UK double adaptor R56

R56 : 16 A / 13 A double adaptor sold per one or 3



UK adaptor economy R55

R55 : 16 A / 13 A adaptor economy sold per one or 3



UK adaptor unit R54

R54 : 16 A / 13 A adaptor unit sold per one or 3



Earth spike RPQ

RPQ : Earth spike to earth your generating set. A 1 meter long galvanized spike delivered with a 2 meters long and 10 mm² gauge cable.



Cans of oil RBH0,5 RBH1

RBH1/RBH0,5 : Box of 20 1L or 0,5 L cans of oil (SAE 15W40)



This product is QUALIGEN certified.

Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After-sales service)

